

CORVETTE® F110 SOLUBLE TEXTILE OIL

DESCRIPTION:

CORVETTE F110 oil is a highly refined mineral-based lubricant for needles and sinkers of circular, and flatbed knitting machines. Easily washable with no stains on textiles and fabrics.

APPLICATION:

CORVETTE F110 range is recommended for the lubrication of:

- Needles, sinkers, and cams of large diameter circular knitting machines.
- Suitable for flat bed knitting machines where an ISO VG 22 lubricant is specified.

BENEFITS:

- Good anti-wear performance & lubrication.
- Prevents built-up of static energy.
- Corrosion protection.
- Ensures longer life of needles and jacks/sinker.
- Very good scourability.

Typical Physical Characteristics

CORVETTE F110	Unit	Method	Typical Results
ISO Viscosity Grade	-	ISO 3448	22
Appearance	-	Visual	Clear & Bright pale-yellow liquid
Kinematic Viscosity@40°C	cSt	ASTM D 445	20.00 – 24.00
Density @ 15°C	kg/l	ASTM D 1298	0.870
Flash Point (COC)	°C	ASTM D 92	185
Pour Point	°C	ASTM D 97	-12

- These characteristics are typical of current production. Whilst future production will conform to CORVETTE specifications, variations in these characteristics may occur.
- For further guidance on Product Health & Safety refer to the appropriate CORVETTE Product Safety Data Sheet.
- Dispose of the used oil to an authorized collection point. Do not discharge into drains, soil, or water.