

CORVETTE® OXLIP GL-3 SAE 140 AUTOMOTIVE GEAR OIL

DESCRIPTION:

CORVETTE OXLIP is a high quality, moderate duty, extreme pressure, all-purpose gear oil for use in automotive, agricultural and industrial applications. Formulated from high quality, paraffinic type base oils, selected mild Extreme Pressure chemical technology and highly effective rust and corrosion inhibitors..

APPLICATION:

CORVETTE OXLIP range is recommended for the lubrication of:

- Wide range of vehicles, including light commercial vehicles and trucks.
- Gearboxes and heavier duty crown and pinion wheels of classic cars.
- Wherever an API GL-3 transmission oil is specified by the vehicle manufacturer.

BENEFITS:

- Compatible with bronze copper brass and non-ferrous metals.
- Minimal wear after a long standstill.
- Exceptional control over foaming, deposit formation and seal compatibility.

SPECIFICATIONS:

- API GL-3.

Typical Physical Characteristics

CORVETTE OXLIP	Unit	Method	Results
SAE	-	SAE J306	140
Kinematic Viscosity		ASTM D 445	
@40°C	cSt	-	320.0
100°C	cSt	-	24.00
Viscosity Index	-	ASTM D 2270	95
Density @ 15°C	kg/l	ASTM D 1298	0.886
Flash Point (COC)	°C	ASTM D 92	280
Pour Point	°C	ASTM D 97	-12

- These characteristics are typical of current production. Whilst future production will conform to CORVETTE specifications, variations in these characteristics may occur.
- For further guidance on Product Health & Safety refer to the appropriate CORVETTE Product Safety Data Sheet.
- Dispose of the used oil to an authorized collection point. Do not discharge into drains, soil or water.

