

CORVETTE® RAZZO 20W-50 SF GASOLINE ENGINE OIL

DESCRIPTION:

CORVETTE RAZZO 20W-50 SF is a mineral-based engine oil formulated using updated additive technology and high-quality virgin base oils designed to meet older vehicles' specifications. The multi-grade oil is suitable for year-round use.

APPLICATION:

CORVETTE RAZZO 20W-50 SF is recommended for the lubrication of gasoline engines, with or without turbochargers.

BENEFITS:

- Controls deposit formation and protects from rust, wear, and corrosion.
- Good high-temperature stability.
- Reduced oil thickening.
- Increased oil life.

Specifications

CORVETTE RAZZO 20W-50 SF Oils meet the requirements of:
API SF

Typical Physical Characteristics

CORVETTE RAZZO 20W-50 SF	Unit	Method	Limits
SAE Grade	-	SAE J300	20W-50
Kinematic Viscosity @ 100°C	cSt	ASTM D 445 -	16.30 – 21.80
Low-Temperature Cranking Viscosity (CCS) (Max.)	cP	ASTM D 5293	9500
Viscosity Index (Min.)	-	ASTM D 2270	120
TBN (Min.)	mgKOH/g	ASTM D 2896	4.0
Density @ 15°C	kg/l	ASTM D 1298	0.8 – 0.95
Flash Point (COC) (Min.)	°C	ASTM D 92	220
High Shear Rate and High-Temperature Viscosity @150°C (Min.)	cP	ASTM D4683	3.7

- These characteristics are typical of current production. Whilst future production will conform to CORVETTE specifications, variations in these characteristics may occur.
- For further guidance on Product Health & Safety refer to the appropriate CORVETTE Product Safety Data Sheet.
- Dispose of the used oil to an authorized collection point. Do not discharge into drains, soil, or water.

