CORVETTE® RAZZO SF GASOLINE ENGINE OIL

DESCRIPTION:

CORVETTE RAZZO SF is a mineral-based engine oil formulated using updated additive technology and high-quality virgin base oils designed to meet older vehicles' specifications. The multi-grade viscosity is suitable for year-round use.

APPLICATION:

CORVETTE RAZZO SF is recommended for the lubrication of gasoline engines, with or without turbochargers.

BENEFITS:

- Controls deposit formation and protects from rust, wear, and corrosion.
- Good high-temperature stability.
- Reduced oil thickening.
- Increased oil life.

Specifications

CORVETTE RAZZO SF Oils meet the requirements of:
API SF

Typical Physical Characteristics

CORVETTE RAZZO SF	Unit	Method	50	20W-50
SAE Grade	-	SAE J300	50	20W-50
Kinematic Viscosity		ASTM D 445		
@100°C	cSt	-	16.30 – 21.80	16.30 – 21.80
Low-Temperature Cranking Viscosity (CCS) (Max.)	cР	ASTM D 5293	-	9500
Viscosity Index (Min.)	-	ASTM D 2270	96	120
TBN (Min.)	mgKOH/g	ASTM D 2896	4.0	4.0
Density @ 15°C	kg/l	ASTM D 1298	0.8 - 0.95	0.8 - 0.95
Flash Point (COC) (Min.)	°C	ASTM D 92	220	220
High Shear Rate and High-Temperature Viscosity @150°C (Min.)	сР	ASTM D4683	-	3.7

- These characteristics are typical of current production. Whilst future production will conform to CORVETT specifications, variations in these characteristics may occur.
- For further guidance on Product Health & Safety refer to the appropriate CORVETTE Product Safety Data Sheet.
- Dispose of the used oil to an authorized collection point. Do not discharge into drains, soil, or water.



كورڤيت راتسو إس إف زيت محركات بنزين

الوصف:

كورڤيت راتسو إس إف زيت محركات معدني تم تركيبه باستخدام تقنية إضافات حديثة وزيوت أساس بكر عالية الجودة مصمم لتلبية مواصفات السيارات القديمة. متوفر منه لزوجة 50-20w (متعدد الدرجات) ليناسب الاستخدام على مدار السنة.

مجالات الاستخدام:

يوصى باستخدام كورڤيت راتسو إس إف في محركات البنزين رباعية الأشواط ذات الشحن الطبيعي أو الجبري.

المميزات:

- يتحكم في تكوين الرواسب ويحمي من الصدأ والبري والتآكل.
 - استقرار جيد في درجات الحرارة العالية.
 - مقاومة تثخين الزيت.
 - إطالة عمر الزيت.

المواصفات:

يفي كورڤيت راتسو إس إف بمتطلبات مواصفة معهد البترول الأمريكي API SF.

