

CORVETTE® SPECTER 15W-50 SL GASOLINE ENGINE OIL

DESCRIPTION:

CORVETTE SPECTER 15W-50 SL is a high-performance, mineral-based motor oil designed for passenger car and light truck gasoline engines operating under a wide range of driving conditions. It is formulated with highly refined mineral base stocks and advanced additive technology to deliver exceptional wear protection, engine cleanliness, and viscosity control.

APPLICATION:

CORVETTE SPECTER 15W-50 SL is recommended for:

- Passenger cars and light trucks
- Gasoline engines (naturally aspirated and turbocharged)
- Four-stroke cycles engines
- Vehicles operating under a wide range of driving conditions, including:
 - Highway driving
 - Stop-and-go traffic
 - Different weather conditions.

BENEFITS:

- Superior Wear Protection.
- Excellent Engine Cleanliness.
- Enhanced Viscosity Control.
- Resists thinning due to high shear forces within the engine, maintaining viscosity and wear protection.

Specifications

CORVETTE SPECTER 15W-50 SL oil meets and exceeds the requirements of:

API SL/CF-4
ACEA A2/B2

Typical Physical Characteristics

CORVETTE SPECTER 15W-50 SL	Unit	Method	Typical Results
SAE Grade	-	SAE J300	15W-50
Kinematic Viscosity @40°C	CSt	ASTM D 445	94.00
100°C	CSt	-	18.50
Viscosity Index	-	ASTM D 2270	140
Apparent Viscosity by CCS @-25°C	mPa.s	ASTM D 5293	5900
TBN	mgKOH/g	ASTM D 2896	8.5
Density @ 15°C	kg/l	ASTM D 4052	0.885
Flash Point (COC)	°C	ASTM D 92	230
Pour Point	°C	ASTM D 97	-30

- These characteristics are typical of current production. Whilst future production will conform to CORVETTE specifications, variations in these characteristics may occur.
- For further guidance on Product Health & Safety refer to the appropriate CORVETTE Product Safety Data Sheet.
- Dispose of the used oil to an authorized collection point. Do not discharge into drains, soil or water.

