

CORVETTE® VEER HIGH-TEMPERATURE GREASE

DESCRIPTION:

CORVETTE VEER high-temperature grease is a premium quality lithium complex grease developed specifically for high-temperature general-purpose industrial applications. Formulated with selected mineral base oils enhanced with functional polymer-based lithium complex thickener, advanced extreme pressure, anti-oxidant, anti-rust, and corrosion inhibitors additive package.

APPLICATION:

CORVETTE VEER high-temp grease is multifunctional grease its uses include but are not limited to:

- Lubrication of heavy-duty components subjected to either oscillating or rotating motion, shock loading, vibration, and the ingress of water.
- Operating temperatures range from -20°C to 150°C

BENEFITS:

- Excellent adhesive & cohesive properties.
- High thermal and oxidation stability.
- Wide operating temperature range -30°C to 150°C.
- Outstanding Load bearing capacity.
- Excellent water resistance.
- Good resistance to rust, corrosion and wear.
- Outstanding extreme pressure properties.
- Resistant to shock, vibrating, and sudden loads.

Typical Physical Characteristics

CORVETTE VEER	Unit	Method	Result
NLGI GRADE	-	SAE J310	2
Soap Type	-	-	Lithium Complex
Base Oil Type	-	-	Mineral
Kinematic Viscosity @40°C	cSt	ASTM D 445	220.0
Cone Penetration Worked @ 25°C	-	ASTM D 217	265-290
Dropping Point	°C	ASTM D 566	>250
4-Ball Wear, Scar	mm	ASTM D 2266	0.4
4-Ball Weld Load	Kg	ASTM D 2596	250

- These characteristics are typical of current production. Whilst future production will conform to CORVETTE specifications, variations in these characteristics may occur.
- For further guidance on Product Health & Safety refer to the appropriate CORVETTE Product Safety Data Sheet.
- Dispose of the used oil to an authorized collection point. Do not discharge into drains, soil, or water.

