

CORVETTE® VISBY EXTREME PRESSURE GREASE

DESCRIPTION:

CORVETTE VISBY greases are premium lubricant greases, formulated from lithium hydroxystearate soap and high-quality base stocks, and are supplemented with special anti-corrosion, anti-wear, and 'Extreme Pressure' additives to achieve excellent performance.

APPLICATION:

CORVETTE VISBY greases EP 2 and EP 3 are multifunctional greases their uses include but are not limited to:

- Antifriction and plain bearings, bushings, and pins that are subjected to moderate to severe loads.
- Heavy-duty slow-running bearings in earth moving, agricultural machinery, and industry.
- Operating temperatures range from -20°C to 130°C

BENEFITS:

- Excellent Boundary Lubrication.
- Outstanding Load bearing capacity.
- Excellent water resistance.
- Excellent stability, as a result of which long service life can be achieved.
- Good resistance to corrosion and wear.
- Excellent pumpability.
- Outstanding high pressure 'Extreme Pressure' properties.
- Resistant to shock, vibrating, and sudden loads.

Typical Physical Characteristics

CORVETTE VISBY	Unit	Method	EP 2	EP 3
NLGI GRADE	-	SAE J310	2	3
Soap Type	-	-	Lithium Hydroxy Stearate	
Base Oil Type	-	-	Mineral	
Kinematic Viscosity @40°C	cSt	ASTM D 445	120.0	120.0
Cone Penetration Worked @ 25°C	-	ASTM D 217	265-295	220-250
Dropping Point	°C	ASTM D 566	>190	>190
4-Ball Wear, Scar	mm	ASTM D 2266	0.4	0.4
4-Ball Weld Load	Kg	ASTM D 2596	250	250

- These characteristics are typical of current production. Whilst future production will conform to CORVETTE specifications, variations in these characteristics may occur.
- For further guidance on Product Health & Safety refer to the appropriate CORVETTE Product Safety Data Sheet.
- Dispose of the used oil to an authorized collection point. Do not discharge into drains, soil or water.



Egyptian co. for manufacturing & trading EMT
info@emt-corvette.com